

# PASA

FLOOR & WALL TILE ADHESIVE



[www.pasaadhesive.com](http://www.pasaadhesive.com)

## PASA SP-500

Epoxy Tile Grout

PASA SP - 500 Epoxy Tile Grout is resin based epoxy tile joint filler which exhibits stain resistant, chemical resistant, hard wearing & impervious properties. Ideal for use in kitchens, bathrooms & wet areas.

### AREAS OF APPLICATION

Ideal for use in kitchens, bathrooms & wet areas.

### FEATURES

- ✔ Easy to mix, apply & use
- ✔ Can be cleaned after application very easily with a damp sponge
- ✔ Ensures longevity of tiles maintaining beauty & strength
- ✔ Certified for use in kitchens & bathrooms by CFTRI,
- ✔ Colour fastness & available in wide range of shades



### BENEFITS



Prevents cracking in tile joints



Stain & Acid Resistant Tile Joint Filler



Waterproof Tile Joints

### HOW TO USE



### DISCLAIMER

The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problem, quality of other materials used and on-site workmanship are factors beyond our control, there are no expressed or implied guarantee/warranty as to the result obtained. The company does not assume any liability or any consequential damage for unsatisfactory results, arising from use of our products.

## PASA FS - 550

Unsanded cement based tile joint filler

FP-OCTO115 Unsanded cement based tile joint filler is water resistant cementitious tile joint filler for all kinds of tiles. It effectively fills the gaps and levels itself to give hard wearing, non-dusting, tile joints.



### AREAS OF APPLICATION

For filling tile joints in bathrooms, kitchens, internal & external floor & wall tiles. Joins upto 5 mm width tiles.

### FEATURES

- ✔ High compressive, tensile & flexural strength
- ✔ Water resistant property
- ✔ Easy to use and clean
- ✔ Available in 18 exciting shades

### BENEFITS



Easy to clean



Durable



Water resistant tile joints

### HOW TO USE



Add 3 to 3.5 parts of Roff Rainbow Tile Mate to one part of water by volume.



Mix to a smooth consistency.



Fill the tile joints by spreading filler paste with rubber trowel such that the entire area of joint gaps are filled.



Remove surplus Roff Rainbow Tile Mate with a damp sponge. Allow 24 hours to dry.

ANR Designer Tiles Pvt Ltd  
16/974 Nida Kanjikode Palakkad, Kerala-678621  
Contact number: +91 89430 08006  
Email: [info@octopuschemicals.com](mailto:info@octopuschemicals.com)



SCAN ME

## COVERAGE CHARTS

### PASA SP - 500

Unsanded cement based tile joint filler

#### PASA Grout Coverage in sq.ft/kg

Tile Dimension (mm)			Joint/ Grouting Width							
Length	Width	Thickness	2	3	4	5	6	8	10	12
300	200	6	77.7	51.8	38.9	31.1	25.9	19.4	15.5	13.0
300	300	6	97.1	64.8	48.6	38.9	32.4	24.3	19.4	16.2
450	300	6	116.6	77.7	58.3	46.6	38.9	29.1	23.3	19.4
600	300	6	129.5	86.3	64.8	51.8	43.2	32.4	25.9	21.6
600	600	8	145.7	97.1	72.9	58.3	48.6	36.4	29.1	24.3
800	800	8	194.3	129.5	97.1	77.7	64.8	48.6	38.9	32.4
1000	1000	10	194.3	129.5	97.1	77.7	64.8	48.6	38.9	32.4
1200	600	10	155.4	103.6	77.7	62.2	51.8	38.9	31.1	25.9
1200	800	10	186.5	124.3	93.3	74.6	62.2	46.6	37.3	31.1
1200	1200	12	194.3	129.5	97.1	77.7	64.8	48.6	38.9	32.4
1600	800	12	172.7	115.1	86.3	69.1	57.6	43.2	34.5	28.8
1800	1200	12	233.1	155.4	116.6	93.3	77.7	58.3	46.6	38.9
25	25	6	8.1	5.4	4.0	3.2	2.7	2.0	1.6	1.3
25	50	6	10.8	7.2	5.4	4.3	3.6	2.7	2.2	1.8
50	50	6	16.2	10.8	8.1	6.5	5.4	4.0	3.2	2.7
100	100	6	32.4	21.6	16.2	13.0	10.8	8.1	6.5	5.4
100	100	10	19.4	13.0	9.7	7.8	6.5	4.9	3.9	3.2

### PASA - FS - 550

Epoxy Tile Grout

#### PASA Epoxy Tile Grout Coverage in sq.ft/kg

Tile Dimension (mm)			Joint/ Grouting Width							
Length	Width	Thickness	2	3	4	5	6	8	10	12
300	200	6	59.8	39.9	29.9	23.9	19.9	14.9	12.0	10.0
300	300	6	74.7	49.8	37.4	29.9	24.9	18.7	14.9	12.5
450	300	6	89.7	59.8	44.8	35.9	29.9	22.4	17.9	14.9
600	300	6	99.6	66.4	49.8	39.9	33.2	24.9	19.9	16.6
600	600	8	112.1	74.7	56.0	44.8	37.4	28.0	22.4	18.7
800	800	8	149.4	99.6	74.7	59.8	49.8	37.4	29.9	24.9
1000	1000	10	149.4	99.6	74.7	59.8	49.8	37.4	29.9	24.9
1200	600	10	119.6	79.7	59.8	47.8	39.9	29.9	23.9	19.9
1200	800	10	143.5	95.6	71.7	57.4	47.8	35.9	28.7	23.9
1200	1200	12	149.4	99.6	74.7	59.8	49.8	37.4	29.9	24.9
1600	800	12	132.8	88.6	66.4	53.1	44.3	33.2	26.6	22.1
1800	1200	12	179.3	119.6	89.7	71.7	59.8	44.8	35.9	29.9
25	25	6	6.2	4.2	3.1	2.5	2.1	1.6	1.2	1.0
25	50	6	8.3	5.5	4.2	3.3	2.8	2.1	1.7	1.4
50	50	6	12.5	8.3	6.2	5.0	4.2	3.1	2.5	2.1
100	100	6	24.9	16.6	12.5	10.0	8.3	6.2	5.0	4.2
100	100	10	14.9	10.0	7.5	6.0	5.0	3.7	3.0	2.5

## Colours of joint filler

Coal black

Slate grey

Pastel brown

Ivory

Pastel grey

Terracotta

Steel grey

Khaki

Snow white

Burly wood

Arctic blue

Dark green

Gold

Sapphire blue

Pastel green

Silver

Crystal

Dark grey

Sky blue

Yellow

Red

## Colours of Epoxy grout



ANR Designer Tiles Pvt Ltd  
16/974 Nida Kanjikode Palakkad, Kerala-678621  
Contact number: +91 90725 55232  
Email: info@pasaadhesive.com

Note:

- (1) This is theoretical coverage.
- (2) For Sq. Mtr./kg coverage, divide mentioned coverage by 10.764.